

## C291X/060060/D4

Steel Block Paviour Access Cover, double seal, 600mm x 600mm clear opening, 100mm tray depth, Loading code X

CLEAR OPENING (MM)	OVERALL TOP OF FRAME (MM)	FRAME DEPTH (MM)	LOAD DUTY
600 x 600	655 x 655	132	Heavy duty

## KEY FEATURES

✓ Hot dipped galvanised for corrosion resistance.

✓ Keyway lifting points are provided on the frame for safe handling.

## SPECIFICATION

### General information

Stock code	C291X/060060/D4
Primary material	Steel
Category	Access cover
Flanges	4
Gross laden vehicle weight	44 tn
Load duty	Heavy duty
Slow moving wheel load (pneumatic tyres)	11.5
Seal type	Double seal

## Standards, classes and groupings

Wrekin loading code X

## Dimensions

Frame shape	Rectangular
Manhole shape	Rectangular
Overall top of frame (A x B)	655 mm x 655 mm
Clear opening (C x D)	600 mm x 600 mm
Frame depth (E)	132mm
Base opening (F x G)	
Overall base of frame	735 mm x 655 mm

## ACCESSORIES

STOCK CODE	DESCRIPTION
KEYSHEAVY	Large cover lifting keys with a standard handle (sold as a pair)

1. Wrekin Products Ltd is continually seeking to improve our products and therefore reserves the right to alter product specifications without prior notice.
2. It is the responsibility of all users to satisfy themselves the above data is current.
3. Installation details are available on request.
4. All Wrekin products are supplied subject to our [Terms and Conditions of Sale](#)



